

AC110-220V 10A STC-3028 Dual LED Temperature Humidity Control Thermostat+Probe

Description :

- Power supply: AC 110-220V,50/60Hz
- Measurement temperature range: -20 ° C ~ +80 ° C
- Measuring humidity range: 00%RH~+100%RH
- Accuracy: $\pm 1^{\circ}\text{C}$ 0.1%RH
- Relay output contact capacity: 10A
- Integrated sensor, line length 1 meter
- Shell material: gray ABS flame retardant plastic shell
- Net weight 120g Gross weight 140g



length: 1 m

SPECIFICATION AND SIZE


Front panel size: 75(L)x34.5(w)(mm)

Mounting size: 71(L)*29(W)(mm)

Product size: 75(L)x34.5(W)x85(D)(mm)

sensor length: 1m (include the probe)

WIRING DIAGRAM



TEMPERATURE SETTING



Long press Δ 3 seconds, the starting temperature value flashes (default 20 °C) Press the plus or minus button to adjust, long press ∇ 3 seconds, stop the temperature value flash (default 30 °C) press the plus or minus button to adjust.

Long press Δ 3 seconds, the starting temperature value flashes (default 40 °C) Press the plus or minus button to adjust, long press ∇ 3 seconds, stop the temperature value flash (default 60 °C) press the plus or minus button to adjust.

Press ∇ 3 seconds to reset the factory settings.



By simultaneously pressing buttons Δ_1 and ∇_1 you are accessing the temperature calibration setting (default 0.0°C). You can make the desired temperature correction by adjusting the flashing value by 0.1, using Δ_1 (UP) and ∇_1 (DOWN) arrows.

By simultaneously pressing buttons Δ_2 and ∇_2 you are accessing the relative humidity calibration setting (default 0.0% RH). You can make the desired humidity correction by adjusting the flashing value by 0.1, using Δ_2 (UP) and ∇_2 (DOWN) arrows.